Serial No.: 10/075,657.

Filed: February 12, 2002

Page : 3 of 14

Amendments to the Claims:

This listing of claims replaces all prior versions and listings of claims in the application:

Listing of Claims:

1. (Currently Amended) A 2x2 optical switch comprising:

- a first port adapted to receive an optical input and generate an optical output;
- a second port adapted to receive an optical input and generate an optical output;
- a switching component group including a singular polarization switch;
- a first component group coupled between the first port and the switch component group;
- a second component group coupled between the second port and the switch component group;

wherein,

when the <u>singular</u> polarization switch is disabled, the switch component group being adapted

to convert pass one or more light beams exiting from the first component group with a first chosen polarization into one or more light beams reentering and reintroduce to the first component group the one or more light beams with the first chosen polarization without changing the polarization of the one or more light beams, and

to convert pass one or more light beams exiting from the second component group with a second chosen polarization into one or more light beams reentering and reintroduce to the second component group the one or more light beams with the second chosen polarization without changing the polarization of the one or more light beams, and

when the <u>singular</u> polarization switch is enabled, the switch component group being adapted

Serial No.: 10/075,657. Filed: February 12, 2002

Page : 4 of 14

to convert one or more light beams exiting from the first component group with the first chosen polarization into one or more light beams reentering entering the second component group with the second chosen polarization, and

to convert one or more light beams exiting from the second component group with the second chosen polarization into one or more light beams reentering entering the first component group with the first chosen polarization.

2. (Original) The 2x2 optical switch of claim 1, wherein

the first component group is adapted to receive the optical input from the first port and generate two light beams with the first chosen polarization entering the switch component group, and to receive two light beams with the first chosen polarization from the switch component group and generate an optical output to the first port; and

the second component group is adapted to receive the optical input from the second port and generate two light beams with the second chosen polarization entering the switch component group, and to receive two light beams with the second chosen polarization from the switch component group and generate an optical output to the second port.

- 3. (Currently Amended) The 2x2 optical switch of claim 1, wherein the <u>singular</u> polarization switch <u>comprises includes</u> a mirror.
- 4. (Currently Amended) The 2x2 optical switch of claim 1, wherein the <u>singular</u> polarization switch <u>comprises</u> includes a liquid crystal cell sandwiched between two transparent conducting plates.
- 5. (Currently Amended) The 2x2 optical switch of claim 1, wherein the <u>singular</u> polarization switch <u>comprises</u> includes a Faraday rotator modulated by a magnetic <u>filed-field</u>.

Serial No.: 10/075,657 Filed: February 12, 2002

Page: 5 of 14

6. (Currently Amended) The 2x2 optical switch of claim 1, wherein the first component group comprises:

- a first birefringent material;
- a structured half wavelength plate coupled to the first birefringent material;
- a second birefringent material coupled to the structured half wavelength plate;
- a half wavelength plate coupled to the second birefringent material; and
- a Faraday rotator coupled to the half wavelength plate.
- 7. (Currently Amended) The 2x2 optical switch of claim 1, wherein the first component group comprises:
 - a first birefringent material;
 - a structured half wavelength plate coupled to the first birefringent material;
 - a second birefringent material coupled to the structured half wavelength plate;
 - a Faraday rotator coupled to the second birefringent material; and
 - a half wavelength plate coupled to the Faraday rotator.
- 8. (Currently Amended) The 2x2 optical switch of claim 1, wherein the switch component group comprises:
 - a reflector coupled to the first switch component group;
 - a singular polarization switch; and
- a polarization beam splitter coupled <u>between</u> to the second switch component group, the reflector and the <u>singular</u> polarization switch.
- 9. (Currently Amended) An optical switch comprising:
 - a first port adapted to receive an optical input and generate an optical output;
 - a second port adapted to receive an optical input and generate an optical output;
 - a switching component group including:
 - a reflector[[,]];

Serial No.: 10/075,657. Filed: February 12, 2002

Page: 6 of 14

a polarization beam splitter coupled to the reflector[[,]]; and

a singular polarization switch coupled to the polarization beam splitter;

a first component group coupled between the first port and the reflector in the switch component group; and

a second component group coupled between the second port and the polarization beam splitter in the switch component group.

10. (Original) The optical switch of claim 9, wherein

the first component group is adapted to receive the optical input from the first port and generate one or more light beams with a first chosen polarization entering the reflector in the switch component group, and to receive one or more light beams with the first chosen polarization from the reflector in the switch component group and generate an optical output to the first port; and

the second component group is adapted to receive the optical input from the second port and generate one or more light beams with a second chosen polarization entering the polarization beam splitter in the switch component group, and to receive one or more light beams with the second chosen polarization from the polarization beam splitter in the switch component group and generate an optical output to the second port.

- 11. (Currently Amended) The optical switch of claim 9, wherein the <u>singular</u> polarization switch <u>comprises</u> <u>includes</u> a mirror.
- 12. (Currently Amended) The optical switch of claim 9, wherein the <u>singular</u> polarization switch <u>comprises</u> includes a liquid crystal cell sandwiched between two transparent conducting plates.
- 13. (Currently Amended) The optical switch of claim 9, wherein the <u>singular</u> polarization switch <u>comprises</u> includes a Faraday rotator modulated by a magnetic <u>filed field</u>.

Attorney's Docket No.: 13854-006001 Applicant: Wei-Zhong Li

Serial No.: 10/075,657 Filed : February 12, 2002

Page : 7 of 14

14. (Currently Amended) The optical switch of claim 9, wherein the singular polarization switch includes an optical filter.

- 15. (Original) The optical switch of claim 14, wherein the optical filter is a tunable optical filter.
- 16. (Currently Amended) The optical switch of claim 9, wherein the first component group comprises:
 - a first birefringent material;
 - a structured half wavelength plate coupled to the first birefringent material;
 - a second birefringent material coupled to the structured half wavelength plate;
 - a half wavelength plate coupled to the second birefringent material; and
 - a Faraday rotator coupled to the half wavelength plate.
- 17. (Currently Amended) The optical switch of claim 9, wherein the first component group comprises:
 - a first birefringent material;
 - a structured half wavelength plate coupled to the first birefringent material;
 - a second birefringent material coupled to the structured half wavelength plate;
 - a Faraday rotator coupled to the second birefringent material; and
 - a half wavelength plate coupled to the Faraday rotator.
- (Currently Amended) The optical switch of claim 9, wherein the second component 18. group comprises:
 - a first birefringent material;
 - a structured half wavelength plate coupled to the first birefringent material;
 - a second birefringent material coupled to the structured half wavelength plate;

Serial No.: 10/075,657 Filed: February 12, 2002

Page : 8 of 14

a half wavelength plate coupled to the second birefringent material; and

- a Faraday rotator coupled to the half wavelength plate.
- 19. (Currently Amended) The optical switch of claim 9, wherein the second component group comprises:
 - a first birefringent material;
 - a structured half wavelength plate coupled to the first birefringent material;
 - a second birefringent material coupled to the structured half wavelength plate;
 - a Faraday rotator coupled to the second birefringent material; and
 - a half wavelength plate coupled to the Faraday rotator.
- 20. (Currently Amended) An optical switch comprising:
 - a first port adapted to receive an optical input and generate an optical output;
 - a second port adapted to receive an optical input and generate an optical output;
 - a switching component group including:
 - a reflector[[,]];
 - a polarization beam splitter coupled to the reflector[[,]]; and
 - a singular polarization switch coupled to the polarization beam splitter;
 - a first component group including:
 - a first birefringent material coupled to the first port[[,]];
 - a structured half wavelength plate coupled to the first birefringent material[[,]];
 - a second birefringent material coupled to the structured half wavelength plate[[,]];

and

- a polarization component subgroup including a coupled half wavelength plate and a Faraday rotator, the polarization component group coupled between the second birefringent material and the reflector in the switching component group; and
 - a second component group including:
 - a first birefringent material coupled to the second port[[,]];

Serial No.: 10/075,657. Filed: February 12, 2002

Page : 9 of 14

and

a structured half wavelength plate coupled to the first birefringent material[[,]]; a second birefringent material coupled to the structured half wavelength plate[[,]];

a polarization component subgroup including a coupled half wavelength plate and a Faraday rotator, the polarization component group coupled between the second birefringent material and the polarization beam splitter in the switching component group.

- 21. (Currently Amended) An optical switch comprising:
 - a first port adapted to receive an optical input and generate an optical output;
 - a second port adapted to receive an optical input and generate an optical output;
 - a switching component group including:
 - a reflector[[,]];
 - a polarization beam splitter coupled to the reflector[[,]]; and
 - a singular polarization switch coupled to the polarization beam splitter;
- a first component group coupled between the first port and the reflector in the switch component group and including a non-symmetrical device; and
- a second component group coupled between the second port and the polarization beam splitter in the switch component group and including a non-symmetrical device, wherein each of the non-symmetrical devices allows for a traversal of light beams along different paths in a respective component group when the light beams pass round trip through the respective component groups.
- 22. (Currently Amended) An optical component comprising:
 - a first birefringent material;
 - a structured half wavelength plate coupled to the first birefringent material;
 - a second birefringent material coupled to the structured half wavelength plate;
 - a half wavelength plate coupled to the second birefringent material; and
 - a Faraday rotator coupled to the half wavelength plate.

Serial No.: 10/075,657. Filed : February 12, 2002

Page : 10 of 14

23. (Original) The optical component of claim 22 wherein the structured half wavelength plate coupled to the first birefringent material plate through a wedge.

- 24. (Original) The optical component of claim 22 wherein the structured half wavelength plate includes two regions of half wavelength plates placed diagonal to each other and two regions of transparent plates placed diagonal to each other.
- 25. (Original) An optical component group comprising:
 - a first birefringent material;
 - a structured half wavelength plate coupled to the first birefringent material;
 - a second birefringent material coupled to the structured half wavelength plate;
 - a Faraday rotator coupled to the second birefringent material; and
 - a half wavelength plate coupled to the Faraday rotator.
- 26. (Original) The optical component of claim 25 wherein the structured half wavelength plate coupled to the first birefringent material through a wedge.
- 27. (Original) The optical component of claim 25 wherein the structured half wavelength plate includes two regions of half wavelength plates placed diagonal to each other and two regions of transparent plates placed diagonal to each other.